



INW2D SERIES



- Caméra IP Jour / Nuit étanche Megapixels
- Projecteur LED IR portée 80 m
- Objectif varifocale 2,8 - 12 mm
- Résolution maxi 2592 x 1920 pixels
- Commutation Jour / Nuit par filtre ICR
- Sensibilité max 0,05 lux
- Menus OSD de paramétrages
- Triple flux H.264, MPEG4, MJPEG
- Enregistreur sur carte SD intégré
- Plug&Play (P2P)
- ONVIF, PPPOE, DHCP, TCP/IP, UDP, RTP/RTCP, RTSP, UPNP, SMTP, RP, SIP, DDNS, DNS, RJ45(10M/100M)
- Compatible Smartphone / iPhone, Android

◆ Specifications ◆

Model No.:	INW2DC10	INW2DC13	INW2DC20	
Camera	Description:	Plastic IR Dome IP Camera		
	Operating System:	Embedded Linux OS		
	Lens:	2.8-12mm Manual Zoom Lens		
	IR LED:	2 pcs, IR Range: 80M		
	Image Sensor:	1/4" 1 Megapixel CMOS	1/3" 1.3 Megapixel CMOS	1/2.5" 2 Megapixel CMOS
Image	Image Resolution:	1280x720	1280x960, 1280x720	2592x1920, 2048x1536, 1920x1080, 1600x1200, 1280x1024, 1280x960, 1024x768, 1280x720
	Frame Rate:	50Hz: 25fps(1280x720) 60Hz: 30fps(1280x720)	50Hz: 25fps(1280x960) 60Hz: 30fps(1280x960)	50Hz: 25fps(1920x1080), 25fps(1600x1200) 60Hz: 30fps(1920x1080), 30fps(1600x1200)
	Min. Illumination:	Color: 0.01Lux @(F1.2, AGC ON), 0 Lux with IR B/W: 0.017Lux @(F1.6, AGC ON), 0 Lux with IR	Color: 0.5Lux @(F1.2, AGC ON) B/W: 0.05Lux @(F1.2, AGC ON)	Color: 0.5Lux @(F1.2, AGC ON) B/W: 0.05Lux @(F1.2, AGC ON)
	S/N Ratio:	>39dB	>44dB	>38.5dB
	Shutter Speed:	1/25s ~ 1/100,000s		
	Day and Night:	IR-cut Filter, auto switch		
Features	AGC:	Auto		
	White Balance:	Auto		
	Exposure:	Auto		
	Settings:	OSD, Brightness, Contrast, Saturation, Acutance via Client Softwares or IE Browsers		
	Ingress Protection:	IP66		
	Video:	H.264 / MPEG4	H.264 / MPEG4 / MJPEG	
Compression	Output Rate:	32 Kbps~16Mbps		
	Audio:	N/A	G.711 / G.726	
	Output Rate:	N/A	64Kbps(G.711) / 16Kbps(G.726)	
	P2P:	Yes		
Network	Storage:	IPC Front-end, SD Card Storage, Back-end NVR and Platform Software Storage		
	Network Protocol:	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP, 802.1x, (SIP, SRTP, IPv6)		
	Interface Protocol:	ONVIF		
	Wifi:	Optional		
	RS485:	N/A		
	Functions:	A Key Recover, Anti-flicker, Dual Stream, Password Protection, Back Light Compensation, Private Area Mask, Watermark		
	Intelligent Alarm:	Motion Detection, Covered, No Network, IP Address Conflict, Full Storage, Storage Error, etc.		
	Mobile View:	Yes		
	Web Management:	Remote View, Control and Settings		
	Interface	Communication Interface:	RJ45 x 1, 10M/100M Self-adaptive Ethernet	
3G:		N/A	Optional(WCDMA, CMDA2000, TD-SCDMA 3G)	
PoE Power:		Optional		
General	Working Temperature and Humidity:	-10°C ~ +60°C, Humidity<90%(no condensation)		
	Power Supply:	DC12V±10%		
	Dimension:	307mm(L) x 120mm(H) x 99mm(D)		
	Weight:	1700g		

