

1/2" High Sensitivity Camera

MR-HS128


2MP x12 Zoom Special IR Camera



Features


- 1/2" 2MP CMOS sensor
- 1080p 30fps, 720p 60fps
- NETWORK, CVBS
- x12 Optical Zoom(7~84mm) & x32 Digital Zoom
- H.264, MPEG-4, MJPEG(Triple Stream & Multi-Codec)
- IR LED 9pcs(Up to 100m)
- Real-time True WDR
- Digital Noise Reduction(2D+3D)
- Digital Slow Shutter
- Digital Image Stabilizer
- Privacy Mask Function
- High Light Compensation
- Defog Function
- ACE(Digital WDR)
- Motion Detection
- IPv4, IPv6 Support
- ONVIF compliant API
- Industry leading latency of 200ms/2Mpix Bandwidth adaptive video streaming
- Dynamic IP support
- SD/SDHC memory slot
- Bi-directional audio support

Installation Guide



Dimensions

Unit : mm



CAMERA	
Image Sensor	1/2" Sony CMOS Sensor
Total Pixels	1952(H) x 1241(V) = 2.42M Pixels
Active Pixels	1937(H) x 1097 (V) = 2.12M Pixels
Scanning System	Progressive Scan
Resolution	Digital : 1080p/30(25)fps, 720p/60(50)fps, 720p/30(25)fps
Min. Illumination	Color(1/30s) : 0.15 lux , BW(1/30s) : 0.01lux Color DSS(1/7.5s) : 0.0375 lux , BW DSS(1/7.5s) : 0.002 lux
S/N Ratio	more than 50dB (AGC off)
Video Output	NETWORK, CVBS

LENS		x12		
Lens Type	x12 Day & Night Zoom Lens			
Zoom Ratio	Optical x12, Digital x32 Zoom			
Focal Length	f = 7.0mm ~ 84mm			
Aperture Ratio	F1.5 (wide) ~ F1.9 (tele)			
Angle Of View (D, H, V)	WIDE	58.3°	51.1°	30°
	TELE	6.5°	5.0°	3.2°

CAMERA FUNCTIONS	
Camera Title	ID / Title / Zoom Ratio / System Message
Day & Night	Auto / Day / Night / Ext-in
WDR/BLC	OFF / WDR / BLC / HLC
ACE	Off / Low / Middle / High
DNR	Auto / Off / Low / Middle / High
Defog	Off / On(Auto / Manual)
Digital Image Stabilizer	Off / On
Motion Detection	Off / On (3 positions)
Privacy Mask	Off / On (24 positions)
Digital Slow Shutter	Off /x2 /x4 (/x8 : 60 or 50fps mode only)
Gain Control	Off / On
White Balance	Auto / One Push / Manual / Indoor / Outdoor
Shutter Speed	1/30(25) ~ 1/30,000 sec
E.Zoom	Off / x2 ~ x32
Digital Flip	Off / H / V / H&V
Digital I/O	1 input / 2 output
Remote Control Interface	RS-422, 485
Protocol	Pelco-D / Pelco- P / WONWOO

NETWORK	
Ethernet	RJ-45 (10/100BASE-T)
Video Compression Format	H.264, MPEG-4, MJPEG
Resolution	1920x1080, 1280x960, 1280x720, 1024x768, 800x600, 720x576, 640x480, 320x240
Streaming Capability	Triple streaming
Alarm	In 1ch / Out 1ch
Audio In / Out	Mic In / Audio Out
Audio Compression Format	G.711 u-law
Audio Communication	Bi-directional audio
IP	IPv4, IPv6
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS
Edge Storage	Micro SD
ONVIF	ONVIF
Webpage Language	Korean, English
Web Viewer	WindowsXP/VISTA/MAC OS X Microsoft Internet Explorer, Firefox, GoogleChrome, Apple Safari

GENERAL	
Power Source	AC24V / DC12V
Power Consumption	1.5A(AC24V) / 2A(DC12V)
Operating Temperature	-20°C~50°C /90% RH
Ingress Protection	IP67/IK10
Material	Aluminum / PC
Dimensions	136(W) x 78(H) X 134(D)
Weight	1.4kg

IP PTZ
IP IR CAM
IP BOX
IP CAM
HD PTZ
HD IR CAM
HD BOX
HD CAM
AHD CAM
CONTROLLER
MULTI TESTER