



Tourelle 30 Kg Télémétrie Pelco TK-30



TK-30

Product Features:

- Support PTZ self-locking, high wind resistance level
- High temperature +70°C, low temperature -35°C
- Aluminum alloy structure design, waterproof grade IP66
- Strong anti-electromagnetic interference ability, suitable for complex environment such as power industry
- High temperature resistance, aging resistance, corrosion resistance, strong wind resistance, waterproof, acid rain resistance
- Support 3D positioning function, fast track target
- High-precision worm gear drive
- Horizontal 360° continuous rotation
- Maximum horizontal speed 15°/S, vertical speed 10°/S.

PTZ Function	Manual speed	Level 0-15°/S ; up and down 0-10°/S
	Maximum speed of preset position	Level 15°/S ; up and down 10°/S
	Preset position accuracy	0.1°
	Horizontal angle	360° continuous
	Vertical angle	-50°~ 50°
	Preset position	255
	Cruise scan	8 groups cruise
	3D positioning	Support
	Watchman	Preset position, cruise
	Power failure recovery	Support
	Telephoto speed limit	Support
Interface	RS485 control interface	Support PELCO-P and PELCO-D
	Analog video	1.0V[p-p] / 75Ω, PAL or NTSC, BNC interface
	Network	10/100M network adaptive, RJ45 adapter
General	Temperature	-35-70℃
	Humidity	0~90% (no condensation)
	Protection level	IP66
	Weight	12KG
	Load	30KG
	Size	272mm×170mm×300mm (L×W×H)
	power supply	DC24V/AC24V
	power	<70W