



MINIATURE MICROPHONE




● Specification

Model	Frequency	S/N Ratio	Impedance	Power Input	Power Current	Output Terminal	Application
MS-3000	20-16000Hz	MORE THAN 58dB	600 ohms 20% (at 1K Hz)	DC 12V	20mA	RCA Male & Female (Optional)	Indoor (5-10 meter)
MS-6000							
MS-3100							
MS-3200							
MS-3600							
MS-3300	20-10000Hz	Maximum 63dB SPL	150 ohms 20% (at 1K Hz)		30mA		

● Ordering Information

Model	Cable Length	Plug Type
MS-3000 MS-3100 MS-3200 MS-3300 MS-3600 MS-6000	50cm	RCA (F)
MS-3000F MS-3100F MS-3200F MS-3300F MS-3600F MS-6000F	180cm	RCA (M)
MS-3000P MS-3100P MS-3200P MS-3300P MS-3600P MS-6000P	180cm	PHONE JAKE
MS-3000M MS-3100M MS-3200M MS-3300M MS-3600M MS-6000M	180cm	RCA (M)
MS-3000W MS-3100W MS-3200W MS-3300W MS-3600W MS-6000W	15cm	4 WIRE

● Ultra Mini Microphone



- High resistance to mechanical shock
- Low vibration sensitivity
- Various responses available
- Lower noise than standard

MS-3300

● Dimension

Model	Dimension
MS-3000	6x18x8 mm
MS-6000	
MS-3100	6x18x4 mm
MS-3200	
MS-3300	
MS-3600	∅10x35