

# COLOR MINI DOME CAMERA

## MCD-G2100NF

## FEATURE



- SONY 1/3" Super HAD Standard-resolution Color CCD
- Compact dome camera **69 (W) x 55 (H) mm**
- 3-Axis gimbal
- 0.1Lux
- Waterproof (IP-65)

## SPECIFICATION

ITEM	NTSC SYSTEM	PAL SYSTEM
Image Sensor	1/3" Sony super HAD CCD	
Effective Pixels	512H x 492V (250K pixels)	500H x 582V (290K pixels)
Scanning System	525 Lines 2:1 Interlace	625 Lines 2:1 Interlace
Scanning Frequency	15.734KHz (H), 59.94Hz (V)	15.625KHz (H), 50Hz (V)
Resolution	380 TV - Lines	
Shutter Speed	1/60 ~ 1/100,000 sec.	1/50 ~ 1/100,000 sec.
S/N Ratio	More than 45dB (AGC Off)	
Sync. System	Internal	
Min. Illumination	0.1 Lux	
Video Output	VBS 1.0 Vp-p (75 ohm Load)	
Lens	Fixed Lens(STD:3.6mm)	
Power Supply	DC12V $\pm$ 10%	
Power Consumption	160mA	
Operating Temp.	-10°C ~ +50°C	