

X-19A/X-19AV



▶ FEATURES

- Distinctive and modern design
- Metal housing for additional strength
- NeoV Optical Filter
- Crisp 700 contrast ratio
- Super wide viewing angle technology
- DVI ready for high quality signal
- S-Video and CVBS inputs (X-19AV only)
- Auto-adjustment for optimal setting
- Kensington® security slot
- VESA standard wall mount



▶ SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	19" (482.6mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.294mm
	Brightness	300cd/m ² (Typical)
	Contrast Ratio	700:1 (Typical)
	Surface Treatments	Hard Coating (2H), anti-glare treatment
	Viewing Angle (H/V)	170°/170° (Minimum)
	Uni-Directional	160° (Typical)
	Display Color	16.7M
	Response Time (R/F)	15ms / 10ms (Typical)
	Frequency (H/V)	H: 30kHz - 80kHz V: 50Hz - 75Hz
	Max. Pixel Clock	135MHz
Input	Analog	15-Pin D-Sub
	Digital (DVI-D)	29-Pin DVI
	S-Video (X-19AV only)	4-Pin Mini Din S-Video
	CVBS (X-19AV only)	CVBS Jack
Connector	Power	3-Pin AC Plug
NeoV Optical Filter	Thickness	3.0mm (0.18")
	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Tilt	Tilt	0° ~ 15°
Mounting	VESA FPMPMI	Yes (100mm)
Dimensions	Net (W x H x D)	444 x 419 x 175 mm (17.5" x 16.5" x 6.9")
	Packing (W x H x D)	540 x 525 x 228 mm (21.2" x 20.7" x 9.0")
Weight	Net Weight	TBD
	Gross Weight	TBD
Regulation Approval	Safety & EMI	FCC, UL, CUL, EPA, TCO 95, TUV/BAURT, CE, NORDIC, NUTEK, BSMI, VCCI, CCC, CB, ISO 13406
	VESA	DDC 1/2B, DPMS
Power	Power AC	100 - 240V, 50 - 60Hz
	Consumption	TBD (On) TBD (Stand-by) TBD (Off)

* All specifications are subject to change without prior notice.

▶ Option



Bras support 6 axes à rappel hydraulique à fixer à la place du pied support livré d'origine

Opto Vision France
ZI Thibaud - 31104 Toulouse
T: 05 61 76 51 11
F: 05 61 76 51 52
www.optovision.fr