



# Caméra IP Jour/Nuit Etanche avec Projecteur IR



WC-118H

- Triple encodage H.264 / MPEG4 / MJPEG
- Double flux simultanés
- Résolution D1 720 x 576 x 25 images/sec
- Boîtier étanche IP 66
- Support mural avec passage de câble sécurisé
- Projecteur IR 40 mètres
- Objectif Varifocale réglable
- Détection de mouvement avec envoi de mails ou FTP
- Compatible IE 8 / SmartPhones / iPhone
- Sortie vidéo de contrôle

## ! Main General Features

- . System: SoC Embedded ARM-Linux
- . Resolution: Full D1(720x576) @ 25fps or less CIF(352x288), QCIF(176x144), .
- . Compression: H.264 / MPEG-4 / MJPEG - Simultaneous Dual Stream
- . Adjustable video data rate
- . Synchronized video compression
- . Simultaneously multiple clients service more than 5Mbps streaming out Maximum 5 users view.
- . Factory setting reset
- . Protocol : DHCP, PPPoE, Dynamic DNS, TCP/IP, UDP, SMTP, UPnP, HTTP, RTSP, DNS client, SNMPv1/v2c, SIP
- . Support HTTP Tunneling (RTSP over HTTP)
- . Provide Dynamic IP server platform for dynamic IP user
- . Watch Dog Timer function
- . IE Browsing supported (ActiveX™)
- . Support NTP time Setting
- . Message in e-mail
- . Provide Real Time Clock function
- . Support 3GPP  
(3G Mobile Phone List: **Nokia Symbian, Windows mobile, Google Android, Apple iPhone**)
- . Hardware OSD of time display
- . **Support Daylight Saving Time**

## ! General Features

- . HTTP port setting, Audio can be disabled (IE)
- . Snapshot, Motion Detect Recording (IE)
- . Auto Recovery when disconnected.(IE)
- . Programmable IP / Subnet / Gateway (IE)
- . Motion Detection Sensitivity: 1~9 (IE)
- . Event: Motion Detect, Video Loss(IE)
- . Action: E-mail and ftp alarm out. (IE)
- . Firmware upgrade over Ethernet (IE)
- . Video quality setting: Contrast, Brightness, Saturation, Hue
- . Windows XP/Vista/7 required ( DirectX™ 9.0Cor Higher)
- . Support Windows Internet Explorer 6.0 / 7.0 / 8.0
- . Language Support : English, French, German, Italian, Spanish,



## ! Camera

- . Image Sensor: 1/3" Sony CCD Sensor
- . Manual Varifocal Lens: f = 3.5 ~ 8mm
- . Horizontal resolution: **520 TVL**
- . IR Distance: 50M
- . Ethernet port: 10/100MBase-T x 1port.
- . Digital I/O
- . Video Output