



Caméras IP Jour/Nuit Etanches avec Projecteur IR



IPCcam-608A



IPCcam-638A

SPECIFICATIONS		IPCcam-608A	IPCcam-638A
CPU	Operation system	Embedded Linux OS	
	Processor	32Bit RSIC Embedded Processor	
Video	Compression format	Motion-JPEG-N	MPEG-4
	Sensor	CMOS 300,000 pixel	1/3 SONY CCD 752 x 582
	Frame rate	25fps PAL 30fps NTSC	
	Resolution	VGA(640*480), QVGA(320*240)	D1(720*576), CIF(352*288)
	Video adjustment	Brightness, contrast, chroma, saturation.	
	Minimum illumination	0.1 Lux/F1.2 Led Off - 0 lux Led On	
	S/N ratio	>48DB (AGC off)	
	Shutter speed	1/50s-1/100.000s	
	WB, BLC	Auto	
Nightvision	Lens	Standard: 6mm Optional: 3.6mm 8mm	
	nightvision	36 F 5 LED IR distance: 25m	24 F 5 LED IR distance: 20 m
Audio		One way audio with AGC	
network	Network interface	RJ-45 10/100Mb self-adaptable Ethernet slot	
	Protocol	TCP/IP, HTTP, ICMP, DHCP, FTP, SMTP, PPPoE, etc...	
	Online visitor	Support 5 visitors at the same time, no limitation with forwarder server.	Support 15 visitors at the same time, no limitation with forwarder server.
	IP mode	Dynamic IP address, static IP address, PPPOE	
Other	Mobile Phone	RTSP 3G cell phone, Nokia Sybiam S60 System, Windows mobile system, iPhone 3G/3GS	
	Shape	Bullet shape, waterproof, aluminium alloy	
	Power	DC12V 1A	
	Temperature	-10~50 °C	
	Waterproof range	Ip66	
	Size	175mm x 74mm x 84mm	214mm x 71mm x74mm
	Weight	N.W.: 392g G.W.: 900g (Note: for real products)	N.W.: 900g G.W.: 1430g(Note: for real products)
	Attachment	Adaptor CD (including manual) bracket	
Alarm	Input / output	1/1	
	Motion detection	Support 16 motion detection regions	
	Alarm action	Support Email photo, FTP photo, FTP video, message,etc.	
System	System requirement	Microsoft Win98 SE/ME/2000/XP/Vista - IE 5.0, NET4.5 or above	
Features	System security	Supports three-level account, password, user authority management	
	DDNS(free)	Free DDNS bounded i.e., http://demo.easynp.cn.	
	Superiority	P2P technology, no user limited, save bandwidth, cell phone monitor	
Certification	CMS(free software)	1,4,9,16,25,36, 64-channel CMS, multi users, centralized monitor, remote record and playback , Skype message alarm, skype telephone alarm	
	Certificate	ISO FCC CE ROHS REED	