

MP-2410 & MP-1205

Feature

- Small & Compact Size design easy installation
- Water-Proof Casing & Counter-Rusty connector ideal for indoor or outdoor use
- High Gain performance /w much wider beamwidth angle than general directional antenna
- High Gain performance /w much farther transmitting or receiving range than general un-directional antenna



Specification

Model	MP-2410	MP-1205
Frequency Range	2.3~2.5 GHz	1.1~1.3GHz
Normal Gain	≥ 10 dBi	≥ 5 dBi
Polarization	Vertical / Linear	
Horizontal Beamwidth	$\geq 55^\circ$	
Vertical Beamwidth	$\geq 56^\circ$	
Front to Back Ratio	≥ 20 dB	
Power Rating	≥ 20 W	
Impedance	50 Ohms Nominal	
Return Loss	≤ -10 dB	
Cable & Connector	CFD-200 (1 Metre) / SMA to SMA	
Cable Attenuation	55 dB / 100 Metre	
Connector	SMA	
Dimension	110 (W) x 110(L) x 27(D) mm	
Weight	300 g	
Bracket	Clamp set	

Standard Shipping Package

- Panel Type Antenna * 1
- Extension Cable*1
- Bracket *1 set

Order Number

MP-2410	2.4GHz / 10dBi Panel Antenna
MP-1205	1.2GHz / 5 dBi Panel Antenna
Each Item Shipping With Extension Cable & All Accessories.	