



Model	WVCSC1E	WVCSC2	WVCSC4
Chipset			
Image Sensor	1/3"AR0130 (2 MP)	IMX323 (2MP)	OV4689 (5 MP)
Main processor	HI3518E	HI3516C	Hi3516D
Resolution	960P	1080P	4MP
Effective Pixels	1305(H)*977(V)	1920(H)*1080(V)	2688(H)*1520(V)
Compression	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG
Electro-	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec		
S/N Ratio	≥52dB		
Scanning System	Progressive		
Output	IP Network		
Focus Length	3.6mm	3.6mm	3.6mm
Focus Control	Fixed	Fixed	Fixed
Ethernet	RJ-45 (10/100Base-T)		
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP		
ONVIF	Support ONVIF 2.4		
P2P	YES, Support QR Code		
POE	Optional, Support IEEE 802.3af		
Video Delay	0.3S (Within the Lan)		
Main Stream 1	1280*960 @25fps	1920*1080 @25fps	2560*1440@20fps
Main Stream 2	/	/	2304*1296@30fps
Main Stream 3	/	/	1920*1080@30fps
Sub Stream 1	720*480@25fps	720*480@25fps	720*480@20fps 720*480@30fps
Sub Stream 2	/	/	/
Sub Stream 3	/	/	/
Tri Stream	/	352*288@25fps	352*288@20fps 352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari		
Smart Phone	iPhone, iPad, Android, Android Pad		
Camera Features			
Day/Night	By automatic IR cut filter switch		
Image Processing	Corridor Pattern, BLC, HDR, Motion detection, WDR, Defog, Privacy masking		
Recording Mode	External : NVR/NAS/CMS/Web		
Language	English, German, Russian, French, Portuguese, Turkish, Spanish, Hebrew, Italian,Neder		
General			
Housing	Plastic		
IR Cut Filter	YES		
Opera-	-10℃ ~ +50℃ RH95% Max		
Sto-	-20℃ ~ +60℃CRH95% Max		
Power Source	DC12V 120mA		
Dimension	120(W)*60(H) mm		
Weight	350g		