

Récepteur de Télémétrie PelcoD



Le PCR-017 fournit les tensions nécessaires au pilotage de zooms et tourelles classiques à partir d'un signal sériel RS-485 au protocole PelcoD.

- Built in PELCO D protocol
- IP65 Weatherproof case
- PAN & TILT control
- Lens control: zoom, focus
- 1 Auxiliary Relay provide for any desired functions: alarm, wash/wipers, lighting
- Easy addressed code setting. (00-99)
- Allows the pan tilt power AC110V/220V/24V, zoom lens power DC12 or 6V (2A-Max.)
- Support heavy duty Pan tilt working power up to 8 Amp (current).
- Built in surge protection
- Support all pan, tilt, zoom lens

Specifications:

SMART PTZ Receiver is designed to control pan & tilt & lens devices via any transmitter systems operating on RS485 with built in PELCO D protocol. The receiver offers system designers the option of using traditional P/T/Z heads for application where it is necessary to specify a range of cameras/lens combinations, support the PTZ data control 100 sets at one time.

<u>Specifications</u>	
Operating Voltage	DC12V
Power Consumption	200mA (Max.)
Transmission	RS485
Cable	CAT 5 Twisted Pair Cable
Transmission Range	1200 meters
Dimensions W x H x D mm	165 x83x 55
STORAGE TEMPERATURE	-30°C~70°C
OPERATION	-10°C~45°C
Contact current.	DC30V 8Amp
	AC250V 8Amp