



TSAX1730



IP68 Explosion Proof Camera Housing

Model	TSAX1730
Size (Ø × L)	
Window Viewing Area (Ø)	73 mm (2.9 in)
Weight	8 kg (17.6 lb)
Material	<ul style="list-style-type: none">• AISI 304 stainless steel (TSAX1730)• AISI 316L stainless steel (TSAX1730-S)
Heater Control	On at 1 °C ± 3 °C (34 °F ± 5 °F) (optional)
Related Products	-

*Design and specifications are subject to change without prior notice.



Features

- IP68, NEMA-6P enclosure rating
- Operating temperature range from -40 °C to 70 °C
- Ex d IIC T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)
- Included wiper and sunshield

Available Models

Model	Material
TSAX1730	AISI 304 stainless steel
TSAX1730-S	AISI 316L stainless steel

Tech Specs

Model	TSAX1730
Atmospheric Pressure	80 kPa to 106 kPa
Operating Ambient Temperature	-40 °C to 70 °C
Relative Humidity	5 % to 95 % noncondensing
Protection Rating	<ul style="list-style-type: none">• Ex d IIC T6 Gb explosion-proof marking• IP68, NEMA-6P enclosure rating
Input Power	<ul style="list-style-type: none">• 24 V AC• 220 V AC, 50 Hz (optional)
Dimensions (W × H × L)	160 mm × 160 mm × 405 mm (6.3 in × 6.3 in × 15.9 in)
Internal Usable	105 mm × 330 mm (4.1 in × 13.0 in)